

Job Name:	Date:
System Reference:	



Indoor Unit: MSZ-EF15NAW-U1



Wireless Remote Controller

SPECIFICATIONS:

Rated Capacity*		
Cooling*1	Btu/h / W	14,000
Heating at 47° F*2	Btu/h / W	18,000

Rating Conditions per AHRI Standard:
 *1 Cooling | Indoor: 80° F(27° C)DB / 67° F(19° C)WB ; Outdoor: 95° F(35° C)DB / 75° F(24° C)WB
 *2 Heating at 47°F | Indoor: 70° F (21° C)DB / 60° F (16° C)WB ; Outdoor: 47° F (8° C)DB / 43° F (6° C)WB

For data on specific indoor units (all ducted, all non-ducted, and both ducted and non-ducted) combinations, see the MXZ Technical and Service Manual.

ACCESSORIES:

Indoor Unit

- Condensate Pump (BlueDiamond X87-711/721; 115/230V)
- Condensate Pump (Sauermann SI30-115/230; 115/230V)
- Anti-allergy Enzyme Filter (MAC-2320FT-E)
- Drain Pan Level Sensor (DPLS2)

Controls

- Wireless Controller (MHK1)
- Wired Remote Controller PAR-32MAA-J (Requires MAC-333IF-E)
- Wireless Interface for kumo cloud™ (PAC-WHS01WF-E)
- Thermostat Interface (PAC-US444CN-1)

Electrical Power Requirements		208 / 230V, 1-Phase, 60 Hz	
Minimum Circuit Ampacity (MCA)	A	1	
Blower Motor (ECM)	F.L.A.	0.67	
Blower Motor Output	W	30	
Moisture Removal	pt./h	3.6	
Field Drainpipe Size O.D.	In.(mm)	5/8 (15)	
Airflow Rate (Lo - Med - Hi - Super Hi - Powerful)			
Cooling	DRY	CFM	205-233-272-314-364
	WET		176-200-234-270-313
Heating	DRY		194-222-275-350-448
Sound Pressure Level (Lo - Med - Hi - Super Hi - Powerful)			
Cooling	dB(A)	28-31-35-39-42	
Heating		28-30-35-41-48	
Unit Dimensions (H x W x D)	In.(mm)	11-3/4 x 34-13/16 x 7-11/16 (298 x 884 x 195)	
Package Dimensions (H x W x D)	In.(mm)	14-1/4 x 38-3/4 x 10-3/4 (362 x 984 x 273)	
Unit Weight	Lbs.(kg)	26 (11)	
Package Weight	Lbs.(kg)	29 (13)	
External Finish	Munsell 1.0Y 9.2/0.2		
Refrigerant Piping (Flared)			
Liquid (High Pressure)	In.(mm)	1/4 (6.35)	
Gas (Low Pressure)		1/2 (12.7)	

